



DEV9108-17

# CG5-10S Replacement Cartridge

## Drop-in Replacement Cartridge for Foodservice Applications



CG5-10S Replacement Cartridge: DEV9108-17

### BENEFITS

- Five micron carbon block reduces dirt and fine particles from drinking water
- Effectively reduces unwanted tastes, odor and chlorine
- High porosity design prevents the cartridge from plugging before its adsorption capacity is exhausted
- Improves the taste of beverages such as fountain drinks and coffee
- Phosphate reduces water-related equipment problems caused by scale build-up from dirt and dissolved minerals
- Helps keep equipment running at peak efficiency and keeps maintenance costs down
- Drop-in design fits most 10" bowls

### INSTALLATION TIPS

- Install vertically so bowls hang down.
- Allow 2-1/2" clearance below the cartridge for easy cartridge replacement
- Make sure O-ring on bowl is sufficiently lubricated
- Always screw on bowls by hand; do not use a housing wrench

### OPERATION TIPS

- Change cartridges on a regular 6 month preventative maintenance program
- Change cartridges when capacity is reached or when pressure decreases
- Always inspect O-ring; change and/or lubricate if necessary
- Always flush the filter cartridge at time of installation and cartridge change

### APPLICATION/SIZING

- For foodservice applications requiring scale reduction
- Drop-in cartridge for taste, odor and sediment reduction
- Capacity: 6,000 gallons (22,800L)

# CG5-10S Replacement Cartridge

## SPECIFICATIONS


Overall Dimensions:  
9.75"H x 2.87" Diameter

Service Flow Rate:  
Maximum 1.67 gpm (6.3 Lpm)

Pressure Requirements:  
30 - 125 psi (2.1 – 8.6 bar), non-shock

Temperature: 40 - 100°F (4.4 - 38°C)

No electrical connection required



The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

## WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



System Tested and Certified by NSF International against NSF/ANSI Standard 42 for the reduction of:

Standard No. 42: Aesthetic Effects  
Chemical Unit  
Taste and Odor Reduction  
Chlorine Reduction

### EVERPURE®

*Worldwide Headquarters:*  
EVERPURE, LLC  
1040 Muirfield Drive  
Hanover Park, Illinois 60133  
Toll Free (800) 323-7873  
Tel (630) 307-3000  
Fax (630) 307-3030  
<http://www.everpure.com>

*In Europe:*  
Pentair Water Belgium B.V./B.A.  
Industriepark Wolfstee  
Toekomstlaan 30  
B- 2200 Herentals  
BELGIUM  
TEL: +32.(0).14.283.500  
FAX: +32.(0).14.283.505

*In Japan:*  
Hashimoto MN Bldg. 7F  
3-25-1 Hashimoto Sagamihara-Shi  
Kanagawa 229-1103  
JAPAN  
TEL: 81.(0)42.775.3011  
FAX: 81.(0)42.775.3015